



**Prime 20 kVA (16 kW)
50 Hz
EU Stage V**

Image shown may not reflect actual configuration

Specifications

Frequency (Hz)	Speed (rpm)	Voltage	Prime		Output Amps (A)	Breaker Rating (A)
			kVA	kW		
50	1500	415 / 240 V	20	16	31	40
		400 / 230 V	20	16	32	
		380 / 220 V	20	16	34	

Cat® C2.2 Diesel Engine	Metric	Imperial (English)
Configuration	Inline 4-cylinder, 4-Stroke-Cycle, Water Cooled, Diesel	
Bore	84 mm	3.3 in
Stroke	100 mm	3.9 in
Displacement	2.2 L	134 in ³
Aspiration	Naturally Aspirated	
Compression Ratio	23.3:1	
Engine rpm	1500	
Fuel System	Indirect Injection	
Governor Type	Mechanical	
Fuel	See Fuel Specification Table	

Benefits & Features

Rental-ready Features

- 12hr dual wall fuel tank with tie down points and robust skid plate base
- Forklift pockets
- Externally certified single point lift
- Coolant and drain lines
- Externally certified spark arrester/silencer
- 50 Hz frequency
- Optimized cable entry for easy hook-up
- Robust busbar connection for lugged cable connection
- Sound isolated side mounted control panel with integrated power distribution access
- AC protected by limit switch on distribution door
- Enclosure protection

Fuel/Emissions Strategy

- EU Stage V

Single-source Supplier

- Factory designed and fully prototype tested with torsional vibration analysis available
- ISO 9001:2000 compliant facility

Cat® C2.2 Diesel Engine

- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight

Cat GCCP1.3 Control Panel

- Fully featured power metering, protective relaying, engine/generator control and monitoring
- Simple user-friendly interface and navigation

Cat LC1100 Generator

- Designed to match performance and output of Cat diesel engines
- Coastal insulation protection
- Self (shunt) excitation

R220 Automatic Voltage Regulator (AVR)

- Provides precise control, excellent block loading, and constant voltage in the normal operating range

Enclosure

- Galvanized sheet steel construction
- Two coat polyester powder-coated finish
- 6 access doors for improved service access
- Secure design with safety glass control panel viewing window and padlockable or keylock access doors
- Fuel fill, battery and controls accessible only through lockable access doors

Environmental Considerations

- Dual wall base tank
- 110% spill containment of all on-board engine fluids
- Bund level alarm
- Low noise enclosure
- Inboard mounted 3-way valve for external fuel connection

Cat Connect

- Fleet management and asset tracking*

Subject to local certifications

Options

- CE socket box with integrated breaker protection
- CEE sockets with protection
- Anti condensation heater 230V AC
- Coolant heater 230V AC
- 12V battery charger
- Earth leakage detection
- Earth Fault detection
- Lube oil sump pump
- Common Alarm
- Volt Free Contacts for Genset running

Standard Equipment

Generator and Voltage Regulation

- Screen protected and drip-proof (IP23), self-regulating, 12-lead, 4-pole, brushless generator
- Sealed-for-life bearing
- Electrical design in accordance with IEC60034-1, EN61000-6, NEMA MG-1.22, and CSA
- Self-excited for self-protection against short circuits
- Insulation System:
 - Class H insulation system
 - Windings are impregnated in a thermo-setting moisture, oil, and acid resisting varnish
 - Heavy coat of anti-tracking varnish for additional protection against moisture or condensation (CIP)
- Waveform distortion, THF, and TIF Factors:
 - Total distortion of voltage waveform with open circuit between phases of Total distortion <5%, on a 3-phase, balanced, harmonic-free load
 - Total distortion <2%, under no load
 - Waveform: NEMA (TIF <50)
 - 2/3 pitch standard on all stator windings

Cat® C2.2 Diesel Engine

- Cat C2.2 heavy-duty, EU-V certified
- Block heater, 220 VAC
- Requires Ultra Low Sulfur Diesel (ULSD) fuel
- Engine Electrical System:
 - 12-volt, DC electrical system
 - 65amp, DC charging alternator
 - Oil pressure, coolant temperature, and coolant level shutdown switches
- Engine Filtration System:
 - Canister type air filter with service indicator
 - Cartridge-type fuel filter with upstream pre-filter and water separator
 - Spin-on, full-flow lube oil filter, requires API CH-4 lube oil (or later)
- Regulator and belt guards

Generator Set Packaging

- Base frame and containment tray
 - Heavy-duty, fabricated steel base frame with specially designed lifting points
 - Spill containment attached to base frame, with leak-detection switch
- Canopy
 - Sound attenuated to 65dBA at 7 m (23 ft)
 - Single door access on each side, and one dedicated access for power distribution and control panel access

Generator Set Packaging (cont'd.)

- Cooling System:
 - Radiator with protective guards
 - Ambient clearance - 45 Deg @ Prime Power
- Electrical System:
 - 12-volt, DC electrical system
 - Battery disconnect switch (Optional)
- Engine and generator mounting
 - Engine and generator are directly coupled by an SAE flange
 - Engine flywheel is flexibly coupled to the generator rotor, with full torsional analysis completed to ensure no harmful vibration will occur in the assembly
 - Anti-vibration pads between engine/generator feet and base frame
- Fuel System:
 - 12-hour runtime @ 75% prime load

Generator Controls and Power Distribution

- Industry leading Caterpillar GCCP1.3 Diesel Generator Set Digital Controller
- Circuit Breaker: 4-pole breaker, 35A with Shunt trip
- Safety switch on hinged main bus cover - trips breaker if cover is opened
- Two-wire, remote start-stop terminals
- Customer auxiliary power connections (Optional):
 - CEE Sockets
 - Each receptacle is protected by a miniature circuit breaker, which also acts as an on/off switch
- Main customer connections:
 - Copper bus bars with phase separators, located behind a protective door with shunt trip switch
 - Bus bars sized for full load capacity of generator set at 0.8 power factor

Quality and Product Support

- Factory load-testing of complete generator set
- Factory test certificate available upon request
- Equipment meets the following standards: IEC60034, EN61000-6
- Full set of operation and maintenance manuals
- walls, ceilings and ducts insulated with precision cut noise insulating materials
- Outlet box mounted with vertical discharge



Fuel Specifications

Specification Standard	Grade Class	Fuel Description
EU Stage V specifies Ultra Low Sulphur Diesel		Ultra-Low Sulphur Diesel Only (ULSD) ULSD with a maximum fuel sulphur level of either 15 or 20 ppm1 is required. Bio-diesel fuel may be used up to B20 (80% standard ULSD with 20% bio-fuel dilution by volume), provided an appropriate approved additive is used

Oil Specifications

Specification Standard	Oil Description
EU Stage V Recommended oil 15W-40 CK-4 1E1867F	CAT DEO-ULS (Preferred)

DEF Specifications

Specification Standard	DEF Description
EU Stage V DEF Requirements ISO22241-1	Diesel Exhaust Fluid



Technical Data

Cat® Generator	
Frame size	LC1114M
Pitch	2/3
No. of poles	4
Excitation	Static regulated, brushless, self excited
Number of bearings	Single bearing, close coupled
Insulation	Class H
Temperature rise	125/40°C
Enclosure	Drip proof IP23
Overspeed capability — % of rated	25%
Voltage regulator	R220
Voltage regulation	Less than ± 0.5%
Wave form deviation	
Telephone Influence Factor (TIF)	Less than 5%
Harmonic Distortion (THD)	Less than 5%

Cat Generator Set		
	TMI Performance No. Units	Prime — 50 Hz P6324B
Power Rating	kVA (kW)	20 (16)
Performance Specification		
Lubricating System Oil pan capacity	L (gal)	6 (1.6)
Fuel System Fuel consumption — 100% Load 75% Load 50% Load Fuel tank capacity Running time @ 75% rating	L/hr (gal/hr) L/hr (gal/hr) L/hr (gal/hr) L (gal) Hr	5.5 (1.45) 4.0 (1.05) 3.0 (0.76) 56 (14.8) 13
Cooling System Ambient capability @ 750 m Engine & radiator coolant capacity Engine coolant capacity	°C (°F) L (gal) L (gal)	45 (113) 10.6 (2.8) 7.0 (1.8)
Air Requirements Combustion air flow at 110% Load	m³/min (cfm)	6.7 (236.6)
Exhaust System Exhaust flow at rated — dry exhaust Exhaust temperature at rated kW	m³/min (cfm) °C (°F)	3.64 (128) 490 (914)



Technical Data (continued)

Cat Generator Set		
	TMI Performance No. Units	Prime — 50 Hz T6316
Noise Rating (with enclosure) ** Sound Power* @ 7 meters @ 75% load @ 7 meters @ 100% load @ 1 meters @ 75% load @ 1 meter @ 100% load	dB(A)	90
	dB(A)	64
	dB(A)	65
	dB(A)	72
	dB(A)	73
	dB(A)	73
Emissions data at 100% Load NOx CO HC PM	g/hp-hr	3.72
	g/hp-hr	1.25
	g/hp-hr	--
	g/hp-hr	--
	g/hp-hr	--

**Guaranteed sound power as per 2000/14/EC

For full Engine & Emissions data please refer to TMI using the engine performance no.


Dimensions			
	Length mm (in)	Width mm (in)	Height mm (in)
Generator Set	1 718 (67.1)	1 001 (39.1)	1 300 (50.78)

Weight	
	Weight — kg (lb)
Lube Oil & Coolant — Empty Fuel Tank	752 (1 654)
Full Fuel Tank	815 (1 793)

Socket Box Option						
Sockets	15A	16A	32A	50A	63A	125A
CEE Form*	-	2x1ph+N+E	2x3ph+N+E	-	-	-

Layout for General Dimensions

Dimensions in millimeters (inches)





Rating Definitions and Conditions

Designed to Meet Specifications: ISO 8528, EN 12601, EN 60204-1, ISO 3046, IEC 60034.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions.

Prime — Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Fuel rates are based on fuel oil of 35° API [16°C (60°F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29°C (85°F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal).

Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding low sulfur fuel and biodiesel capability, please consult your Cat dealer.

www.Cat.com/rentalpower

©2023 Caterpillar All rights reserved.

Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.