

## CAT 3512B (50 Hz) Generator Set

<https://www.zeppelin.com/de-en/powersystems>



Minimum Rating	1320 kVA
Maximum Rating	1875 kVA
Emissions/Fuel Strategy	Low Fuel, Low Emissions
Voltage	380 to 415 Volts
Frequency	50 Hz
Speed	1500 rpm
Duty Cycle	Standby, Mission Critical, Prime
Engine Model	3512B TA, V-12, 4-Stroke Water-Cooled Diesel
Bore	170 mm
Stroke	190 mm
Stroke - HD	215 mm
Displacement	51,8 l
Displacement - HD	58,56 l
Compression Ratio	14.0:1 Std 15.5:1 HD
Aspiration	TA
Fuel System	Electronic Unit Injection
Governor Type	Adem™3
Length - Minimum	5.249 mm
Length - Maximum	5.469 mm
Width - Minimum	1.975 mm
Width - Maximum	2.286 mm
Height - Maximum	2.367 mm
Dry Weight - Genset (minimum)	11.350 kg
Dry Weight - Genset (maximum)	12.180 kg
Maximum Rating	1.875 kVA
Minimum Rating	1.320 kVA
Rated Speed	1500 rpm

**This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.**

## CAT 3512B (50 Hz) Generator Set

