

CAT 3516B (50 Hz) Generator Set

<https://www.zeppelin.com/de-en/powersystems>



Minimum Rating	2000 kVA
Maximum Rating	2500 kVA
Emissions/Fuel Strategy	Low Fuel, Low Emissions
Voltage	380 to 11000 Volts
Frequency	50 Hz
Speed	1500 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3516B TA, V-16, 4-Stroke Water-Cooled Diesel
Bore	170.0 mm
Stroke	215.0 mm
Displacement	78.08 l
Compression Ratio	15.5:1
Aspiration	TA
Fuel System	Electronic unit injection
Governor Type	Adem™3
Length - Minimum	5928.0 mm
Length - Maximum	6377.0 mm
Width - Maximum	2286.0 mm
Height - Maximum	2367.0 mm
Dry Weight - Genset (minimum)	14470.0 kg
Dry Weight - Genset (maximum)	18290.0 kg
Maximum Rating	2500.0 kVA
Minimum Rating	2000.0 kVA
Rated Speed	1500 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

CAT 3516B (50 Hz) Generator Set

