

## CAT 3516C Generator Set

<https://www.zepelin.com/de-en/powersystems>

Minimum Rating	1650 ekW
Maximum Rating	2500 ekW
Emissions/Fuel Strategy	U.S. EPA Cert., Tier 2
Voltage	380 to 13800 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous
Engine Model	3516C, ATAAC, V-16,4-Stroke Water-Cooled Diesel
Bore	170.0 mm
Stroke	190.0 mm
Stroke - HD	215.0 mm
Displacement	78.0 l
Compression Ratio	14.7:1
Aspiration	TA
Fuel System	Electronic unit injection
Governor Type	Adem™3
Length - Minimum	7229.0 mm
Length - Maximum	7495.0 mm
Width - Minimum	2379.0 mm
Width - Maximum	2569.0 mm
Height - Minimum	2958.0 mm
Height - Maximum	3009.0 mm
Dry Weight - Genset (minimum)	16275.0 kg
Dry Weight - Genset (maximum)	17590.0 kg
Rated Speed	1800 rpm
Minimum Rating	1650.0 kVA
Maximum Rating	2500.0 kVA

**This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.**

## CAT 3516C Generator Set

