

CAT 3516C Tier 4 Final
Serial No.: 18500392<https://www.zeppelin.com/de-en/powersystems>

Minimum Rating	1650 ekW
Maximum Rating	2500 ekW
Emissions/Fuel Strategy	U.S. EPA Certified
Voltage	480 to 13800 Volts
Frequency	60 Hz
Speed	1800 rpm
Duty Cycle	Standby, Mission Critical, Prime
Engine Model	3516C HD, ATAAC, V-16, 4-Stroke Water-Cooled Diesel
Bore	170.0 mm
Stroke	215.0 mm
Displacement	4764.72998 l
Compression Ratio	14.7:1
Aspiration	TA
Fuel System	Electronic unit injection
Governor Type	ADEM™A4
Length - Minimum	6796.6001 mm
Length - Maximum	7037.5 mm
Width - Minimum	2378.69995 mm
Width - Maximum	2569.0 mm
Height - Minimum	2964.80005 mm
Height - Maximum	3019.0 mm
Dry Weight - Genset (minimum)	16874.0 kg
Dry Weight - Genset (maximum)	18270.0 kg
Maximum Rating	2500.0 kVA
Minimum Rating	1650.0 kVA
Rated Speed	1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.

CAT 3516C Tier 4 Final
Serial No.: 18500392

