

CAT C15 ACERT Tier 2 Oilfield Diesel Generator Set
Serial No.: 18550898

null null

<https://www.zepelin.com/de-en/powersystems>



Maximum Rating	455 ekW (570 kVA)
Minimum Rating	292 ekW (365 kVA)
Emissions/Fuel Strategy	U.S. EPA Tier 2, U.S. EPA Tier 3, EU Stage II, China Phase II
Aspiration	Turbocharged, air-to-air aftercooled
Manifold Type	Dry
Bore	137.2 mm
Stroke	171.39999 mm
Displacement	15.2 l
Engine Control and Protection	ADEM A4
Generator Set Control	EMCP 3.1
Generator	SR4B
Fuel System	MEUI
Frequency - Speed	50/60 Hz (1500/1800 rpm)
Fuel	Diesel
Length	3518.0 mm
Width	1524.0 mm
Height	2110.0 mm
Weight	4760.0 ton (US)
Maximum Rating	570.0 kVA
Minimum Rating	365.0 kVA
Rated Speed	1500/1800 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.