

CAT C9.3 Marine Generator Set

<https://www.zepelin.com/de-en/powersystems>



Excitation	Permanent Magnet
Minimum Rating	185R kW (231 kVA) at 50hz, 224R kW (280 kVA) at 60hz
Maximum Rating	250R kW (313 kVA) at 50hz, 300 kW (375 kVA) at 60hz
Frequency	50 Hertz & 60 Hertz
Speed	1500 rpm @ 50Hz & 1800 rpm @ 60Hz
Aspiration	Turbocharged Aftercooled
Bore	105 mm
Stroke	135 mm
Fuel System	Common Rail
Engine Model	C9.3
Emissions/Fuel Strategy	EPA Tier 3, IMO II, EU IW
Height	1.436 mm
Length - Engine	2.170 mm
Weight - Approximate	2.367 kg
Width - Engine	1.260 mm
Insulation	Class H
Drip Proof	IP23
Voltage Regulator	approx. 0.5%
Number of Leads	12-Lead 2 wires per lead
Maximum Rating	313 kVA
Minimum Rating	231 kVA
Rated Speed	1500 rpm @ 50Hz & 1800 rpm @ 60Hz

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.