

CAT Cat® C18 Industrial Diesel Engine

<https://www.zeppelin.com/de-en/powersystems>



| | |
|--|---|
| Maximum Power | 597 kW |
| Maximum Torque | 3.655 Nm @ 1600 rpm |
| Rated Speed | 1800-2100 rpm |
| Minimum Power | 429 kW |
| Emissions | China Nonroad III, U.S. EPA Tier 3 equivalent or U.S. EPA Tier 2 equivalent, EU Stage IIIA equivalent, or Non-certified |
| Engine Configuration | Inline 6, 4-Stroke-Cycle Diesel |
| Bore | 145 mm |
| Stroke | 183 mm |
| Displacement | 18,1 l |
| Compression Ratio | 16.3:1 |
| Aspiration | Turbocharged Aftercooled (TA) |
| Combustion System | Direct Injection |
| Rotation from Flywheel End | Counterclockwise |
| Aftertreatment | - |
| Length | 1.414 mm |
| Width | 974 mm |
| Height | 1.257 mm |
| Weight - Net Dry - Basic Operating Engine Without Optional Attachments | 1.673 kg |

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.