


CAT Cat C280-16 Marine Generator Set

<https://www.zeppelin.com/de-en/powersystems>



Minimum Rating	4700 ekW (5875 kVA)
Maximum Rating	4840 ekW (6050 kVA)
Frequency	50 Hz or 60 Hz
Speed	1000 rpm (50 hz) or 900 rpm (60 hz)
Aspiration	Turbocharged-Aftercooled
Bore	280 mm
Stroke	300 mm
Displacement	296 l
Governor Type	Electronic
Fuel System	EUI
Compression Ratio 50 Hz	13,1
Compression Ratio 60 Hz	13:1
Engine Model	Vee 16, 4-Stroke-Cycle Diesel
Emissions/Fuel Strategy	EPA Tier 2, IMO II
Length	9.314 mm
Width	1.990 mm
Height	4.167 mm
Weight	31000 kg/ 68343 lb (engine dry weight), 18145 kg/ 40000 lb (generator weight)
Minimum Power	0 kW
Maximum Power	15.000 kW
Maximum Rating	6.050 kVA
Minimum Rating	5.875 kVA
Rated Speed	1000 rpm (50 hz) or 900 rpm (60 hz)

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.