

## CAT Cat C32 Generator Set (IMO III)

<https://www.zeppelin.com/de-en/powersystems>



Minimum Rating	219 ekW
Maximum Rating	940 ekW
Frequency	60hz
Rated Engine Speed	1500 rpm
Configuration	Vee-12, 4-stroke-Cycle-Diesel
Aspiration	Turbocharged-aftercooled aspiration
Bore	145 mm
Stroke	162 mm
Displacement	32,1 l
Governor	Electronic (A5 ECM)
Emissions	IMO III emissions certified (SCR required)
Length	167.2 in/4245 mm (minimum), 226.1 in/5742 mm (maximum)
Width	59.9 in/1521 mm (minimum), 89.8 in/2280 mm (maximum)
Height	70.4 in/1747 mm (minimum), 92.8 in/2356 mm (maximum)
Package Dry Weight	15721 lb/7131 kg (minimum), 21998 lb/9978 kg (maximum)
Refill Capacity	Lube Oil System w/ oil filter change: 146 L (38.5 gal)
Oil Change Interval	750 hrs
Cooling	Heat exchanger, keel or radiator cooled
Generator	SR5 - Form Wound
Maximum Rating	940 kVA
Minimum Rating	219 kVA
Rated Speed	1500 rpm

This offer is without obligation. The offer is based on our General Terms and Conditions of Sale and Delivery. Changes to equipment and accessories required for technical reasons may be made at any time. Subject to errors, changes and intermediate sale. Statutory value-added tax shall be added to all price.